

CustomSuitsShirts.com Measurement Instructions – Complete this form to use when placing your online order.

CustomSuitsShirts.com wants you to achieve maximum satisfaction with your custom clothing experience and we urge you to carefully follow the recommendations below:

- Wear a suit and dress shirt while being measured - please do NOT wear jeans or casual clothing to be measured, as the measurements obtained could be incorrect.
- Take all measurements snugly, but NOT tight & allow room for 1 finger to slide around inside of tape.
- Take 3 digital photos (front, profile and rear with no coat on) are highly recommended to be sent to us via an order confirmation e-mail that we will send you after your order has been placed.
- Take the pictures wearing a dress shirt and dress trousers, with the collar buttoned at the neck.
- Take a picture of any fit issues you may have of your current suit, with the jacket on.
- Have someone carefully take all measurements of you & take each measurement at least 3 times recommended for accuracy.
- Make any comments in special instructions on your order if you would like to have a measurement changed: added or subtracted to. Example: please add 1" to half girth measurement as my coat is too tight to button properly.
- Add any comments to special instructions concerning any fit issues that you have experienced in the past, such as a collar roll on your jackets.

By following these recommendations carefully, you will increase the fit accuracy of your custom garment.

Over arm: _____

Place the tape horizontally over both arms at the most prominent part of the bicep. Make sure the tape is parallel to the floor.



Coat waist: _____

Measure around fullest part of the stomach.



Seat : _____

(front view) Place tape horizontally around fullest part of seat & take a loose measurement.



Chest : _____

Raise arms up , place the tape horizontally under the armpits, across the fullest part of the chest & measure . Make sure the tape is firm across the chest, so the tape does not fall down.



Waist : _____

Lower trousers down 1" without unfastening trousers & measure under waistband of trousers



Seat : _____

(side view)



Bicep: _____

Place tape around fullest part of flexed bicep.



Thigh: _____

(front view) Place tape around fullest area of thigh



Trousers Inseam: _____

Place the trousers on a flat, smooth surface & open the trousers so that the one leg is draped back towards the waistband. Take the tape & place @ the top of the center inside seam of the trousers & measure from the crotch straight down to the bottom of the trousers.



Yoke: _____

Take the shoulder measurement from one shoulder seam, across the top of the shoulder, to the other shoulder seam and add 1/2".



Knee: _____

Place tape at knee area & take measurement from rear trouser crease to front trouser crease



Button position for Coat or vest: _____

(optional on coat) Measure from shoulder seam down to desired placement of top button of coat or vest



Outseam: _____

Pull your trousers up so that they are sitting where your natural waist line is. Place the tape at the top of the waistline & run the tape down to the bottom of the floor, deduct 1".



Bottom: _____



Vest front length: _____

Measure from shoulder seam down to bottom of belt, add 4.5"



Vest back length: _____

Measure from bottom of shirt collar to bottom of belt, add 2.5"



Measure felt under rear collar down the back length of coat to bottom.



Point to point: _____

With coat on, measure shoulders straight across from left shoulder seam to right shoulder seam



Sleeve Inseam: _____

Lay coat on flat surface & measure inside seam of coat sleeve from armhole to edge of sleeve.



Half back: _____

Measure back of coat from where armhole meets the sleeve seam across back to center seam



Half Girth: _____

Lay coat on flat surface & measure from center back seam across to top of middle (2nd) button to coat edge



Coat length: _____